



REDPATH FLEET OF RAISE DRILLS

Extended Height	120" 1/2 (3.06 m)
Footprint Width	54" 1/2 (1.38 m)
Footprint Depth	41" (1.04 m)
Mass	9,000 lbs (4,082 kg)
Maximum Arm Load	10,000 lbs (4,536 kg)

*All measurements without rod handler.

Thrust System

Type	Hydraulic cylinders
Maximum Upream Force	100,000 lbs (445 kN)

Rotation System

Type	Hydraulic drive
Maximum Torque	20,000 ft / lbs (27.1 kN.m)

Nominal Parameters

Pilot Hole Diameter	9" (228.6 mm)
Drill Pipe Diameter	5 3/4" (146.1 mm)
Hole Diameter Upream	42" (1.07 m)
Raise Angle	45 - 90°

Options

Redtrax Transporter	Yes
Erector System	Yes

* Electrical systems built to suit regional requirements.

* Deflectors are optional, and must be added to overall height of machine.

Note: Drill specifications including thrust, torque, weights and dimensions are approximate and may vary from those provided.



- Designed for boxhole and upream applications.
- Equipped with loading pockets.
- Highly mobile – can be moved using scoops or loaders.



REDTRAX COMPATIBLE

REDBORE 30

The Redbore 30 was designed specifically for rapid boxhole development. It is the lightest, most compact drill in the blindhole and boxhole market. The drill's energy efficient power pack and operating console have been combined, making this unit a highly mobile and productive package.

The machine is equipped with loading pockets and can be moved by most underground scoops and loaders, which greatly minimizes collar-to-collar downtime.

Nominally, the Redbore 30 is capable of boring 42" (1.06 m) diameter.

